



TECHNICAL DATA SHEET

EAZYTape MACHINE USE HOTMELT 2 MIL / 1000 YRDS

Document No	CPA-TDS-GA01
Release Date	10.10.2023
Revision Date	
Revision No	

PRODUCT GENERAL SPECIFICATION:

PRODUCT CODE:	EZ50100
PRODUCT DESCRIPTION:	HOTMELT HAND PARCEL PACKAGING TAPE
MAIN USAGE:	ALL TYPE OF PARCEL SEALING
PRODUCT TYPE	UPPER MEDIUM PERFORMANCE MULTI USE PACKAGING TAPE
FILM MATERIAL	POLYPROPYLENE BOPP
FILM DENSITY	0.9 GR/ M3
ADHESIVE MATERIAL	HOTMELT
CORE MATERIAL	PAPER
CORE INNER DIAMETER	76 MM
COLOR	TRANSPARENT

PHYSICAL VALUE

TEST	VALUE	TOLERANCE	TEST METHOD
FILM WIDTH	1.88 INCH – 48 MM	+,- 3%	ISO 4592
LENGTH	1000 YARDS / 914 MTS	+,- 3%	ISO 4592
TOTAL THICKNESS	2 MIL – 50 MICRON	+,- 10 %	ISO 4591 / ASTM E252
THICKNESS OF FILM	28 MICRON	+,- 10 %	ISO 4591 / ASTM E252
ADHESIVE COATING WEIGHT	22 GR /m ²	+,- 10 %	ISO 4591 / ASTM E252
WEIGHT OF ROLL	380 GR	+,- 10 %	ISO 4591 / ASTM E252





MECHANICAL PROPERTIES

TEST	VALUE	TOLERANCE	TEST METHOD
ELONGATION AT BREAK	1460 %	+,- 3%	AFERA5004
TENSILE STRENGTH AT BREAK	150 N / 25 mm	+,- 10 %	AFERA5004
180 C PEELING ADHESION	18 N / 25 mm	+,- 10 %	AFERA5001
LOOP TACK	26 N / 25 mm	+,- 10 %	FINAT FTM-9

PACKAGING

BOX	YES
PCS PER BOX	6
BOX DIMENSIONS	235*235*297 mm
PCS / PALLET	
PALLET DIMENSIONS	
SELF LIFE	12 MONTHS
STORAGE	DRY, 15-26 C

This data may vary without any notice – the updated typical sheets can be forwarded at any time. Since many different factors may influence the products' performance, we recommend that you test the product for your application to make sure that it is fit for purpose. This information does not express or imply a performance guarantee in any way whatsoever. We remain at your disposal for any further information.

